



KKWO19B Kordin Industrial Estate  
Paola PLA3000  
Malta  
Europe  
Tel: +356 21 251 685  
Fax: +356 21 239836  
Email: [info@tuaeng.com](mailto:info@tuaeng.com)  
Web: [www.tuaeng.com](http://www.tuaeng.com)

---

## **SF WATER SOFTENERS Specification Sheet**



Due to ongoing developments specifications are subject to change without notice.

Our SF range of standard water softeners are manufactured using high quality GRP vessels and Pentair Autotrol Valves. Apart from our standard range we can manufacture different and much larger systems to suit your needs. Other valves including SAITA™, FLECK™, and ERIE™ are also available upon request.

CABINET TYPE		Capacity	Controls	Connection	Standard Valve	Dimensions
Model	Description	m <sup>3</sup> F <sup>o</sup>			Model	mm
SFC008T	8 ltr cabinet	40 - 50	Time	3/4" with mixer	Autotrol 255/740	240 x 435 x 440
SFC021T	21 ltr cabinet	100 - 120	Time	3/4" with mixer	Autotrol 255/740	320 x 500 x 1140

SIMPLEX		Capacity	Controls	Connection	Valve	Dia & height	Salt Tank
Model	Description	m <sup>3</sup> F <sup>o</sup>			Model	GRP vessel mm	Itrs
SFS033V	33ltr simplex	160-210	Volumetric	1" with mixer	Autotrol 255/760	250 x 1100	140
SFS060V	60ltr simplex	300-380	Volumetric	1" with mixer	Autotrol 255/760	330 x 1370	140
SFS100V	100ltr simplex	500-650	Volumetric	1" with mixer	Autotrol 268/760	400 x 1320	340
SFS170V	170ltr simplex	850-1020	Volumetric	1" or 1 ¼ "	Autotrol 278/762	460 x 1650	460
SFS220V	220ltr simplex	1100-1320	Volumetric	1" or 1 ¼ "	Autotrol 278/762	530 x 1575	670

DUPLEX		Capacity	Controls	Connection	Valve	Dia & height	Salt Tank
Model	Description	m <sup>3</sup> F <sup>o</sup> /vessel			Model	GRP vessel mm	Itrs
SFD60V	60+ 60ltr Duplex	300-380	Volumetric	1"including manifold	Autotrol 255/764	330 x 1370	140
SFD100V	100+100ltr Duplex	500-650	Volumetric	1"including manifold	Autotrol 268/764	400 x 1320	340
SFD170V	170+170ltr Duplex	850-1020	Volumetric	1" or 1 ¼ "	Autotrol 278/764	460 x 1650	460
SFD220V	220+220ltr Duplex	1100-1320	Volumetric	1" or 1 ¼ "	Autotrol 278/764	530 x 1575	670

**NOTES:**

Highlighted items are normally available from stock.

Other sizes available upon request.

60ltr vessels or smaller are pre-loaded with resin. Larger vessels have to be loaded on site by client.

Other valve types available on request.

Maximum available mean capacity with GRP vessels is 12,000 m<sup>3</sup>F<sup>o</sup> per vessel.

For further information contact **OUR** local agent or our manufacturing facility:

local agent

**KKWO 19B KORDIN INDUSTRIAL ESTATE  
 PAOLA PLA3000, MALTA, EUROPE  
 TEL(+356) 21 25 1685 FAX (+356)2 1 239836  
 E-MAIL:info@tuaeng.com WEB-SITE: www.tuaeng.com**

Due to ongoing developments specifications are subject to change without notice.