

MODEL: RO 200

Description

The **RO200** range is a light commercial reverse osmosis water purification systems that provides a high capacity with a low cost. It utilizes state of the art technology and components to provide you with safe, good quality and refreshing water.

The **RO200** meets all the water quality needs in terms of the removing odour, taste, chemical contaminants whilst guaranteeing fresh supply of water throughout. It also reduces the following hard water contaminants that may be present in your water; lead, copper, barium, chromium, mercury, sodium, cadmium, fluoride, nitrite, nitrate and selenium.

This system has been designed small in size but big in performance.



Standard Features

- ✦ 5 Stage Filtration System
- ✦ Maximum daily capacitance is up to 757 litres per day- based on 500mg/l feed. This varies according to local conditions and depends on the feed water.*
- ✦ 41.6 Litre, Water Storage Tank with Tank Ball Valve
- ✦ FDA Approved Polypropylene Made Flat Cap Housings
- ✦ Booster Pump; 24V with 230Vac 50Hz adapter
- ✦ Build in Electrical Shut-off Valve to prevent any damage of the membrane
- ✦ Self-Piercing Saddle Valve & Feed Water Quick Connector
- ✦ Drain Saddle Valve
- ✦ Attractive Long Reach European designed , Model 101 Faucet



Model 101

Application

The **RO200** are ideal for residential or light commercial applications. These systems can be utilised for small industrial premises, offices, restaurants, shopping centres, schools and hotels.

Dimensions / Weight

RO unit: 50cm (L) X 24cm (W) X 80cm (H)

Tank: 40cm (L) X 40cm (W) X 58cm (H)

Total Weight: 42kg

** In Malta the daily capacity is expected to be considerably less*

MODEL: RO200 TECHNICAL INFORMATION

Stage 1 – 5 Micron Spun-polypropylene Sediment Filter

With only 5 Micron Rating, it is effective in removing dirt, rust and sand particles.

Stage 2 – Granular Activated Carbon Filter

It removes 99% of the chlorine and organic chemicals. It provides enhanced reduction of taste, odour and colour.

Stage 3 – Block Carbon Filter

It further removes any organic chemicals. It provides enhanced reduction of taste, odour and colour.

Stage 4 – Reverse Osmosis Membrane

It consists of a thin film composite (TFC) high quality membrane that processes 757 litres per day. It removes the following hard water contaminants that may be present in your water; lead, copper, barium, chromium, mercury, sodium, cadmium, fluoride, nitrite, nitrate and selenium.

Stage 5- Inline Post Carbon Filter

This carbon post filter removes unpleasant tastes and odours in order to enhance the quality of the drinking water. These are NSF approved post carbon to guarantee the taste of water.

Materials of Construction

Item	Material
Membrane and Filter Housings	100% polypropylene, NSF Listed material.
Inline Post Carbon Filter	Polypropylene housing containing activated carbon
Booster Pump	Steel body with Polypropylene pump head
Solenoid Valve	Brass
Tank	Polypropylene vessel will never rust, chip or dent. Reliable diaphragm design allows for maximum discharge of water
Flow Restrictor	100% polypropylene. No metal to water contact.
Connectors & tubing	100% polypropylene, NSF Listed material
Mounting Brackets	Heavy-duty powder coated white steel